

BBB Windlass Chain - G30



BBB is a low carbon steel chain designed with short, compact calibrated links suitable for windlasses and general anchoring. Check manufacturer's specification prior to purchase.

Finish: Hot Dip Galvanized Packaging: Full Drums

Exceeds NACM, RR-C-271D specifications

Trade Size in.	Wire Diameter		Inside Dimensions				Working Load Limit	
	mm	in.	Length		Width		kg-force	pound-force
			mm	in.	mm	in.		
1/4	7.1	0.281	22.1	0.87	10.92	0.43	590	1300
5/16	8.7	0.344	25.4	1.00	12.7	0.50	862	1900
3/8	10.3	0.406	27.69	1.09	15.75	0.62	1202	2650

Trade Size in.	Part ID	Full Drum			
		Weight		Length	
		kg	lbs	m	ft.
1/4	10315911	261	576	243.84	800
5/16	10315912	274	605	167.64	550
3/8	10315913	283	624	121.92	400

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications

Packaging

Full Drum



	DIA		Height	
	in.	cm	in.	cm
Full Drum	16½"	41.9	29"	73.7
Half Drum	16½"	41.9	15"	38.1
Plastic Pail	12" x 9½"	30.5 x 24.1	14½"	36.8

Half Drum



Plastic Pail

