

venting prevent moisture and mildew > >



Weather-Tight Vent

(DS-683)

Allows air circulation under shrink wrap covers and is water resistant when installed horizontally or vertically. Easy installation using the one-piece pull tab that exposes over 15 square inches of adhesive. UV additives for long life in all climates. Available in black or white, with or without screen.





Self-Piercing Louvered Vent

(DS-STEALTH)

The Stealth vent is easily installed by simply piercing the shrink wrap cover. Provides protection from condensation, heat build-up and mildew from trapped moisture. Seals itself to prevent rain and snow from getting under the cover. Made of lightweight and durable plastic.





Wind-Powered Vent

(DS-683WP)

Dr. Shrink has once again re-invented the Weather-Tight vent. We added anemometer cups to spin blades, creating the DS-683WP Wind-Powered Vent. It moves air under the shrink wrap cover with even the slightest breeze and can circulate air 24 hours per day. The cups can be rotated to either deliver air or remove it, maximizing air flow under the cover and eliminating moisture buildup. Available in blue or white.





Round Airlette Vent

(DS-062A)

Three-part self-adhesive vent that firmly sticks to shrink wrap and can withstand all weather conditions. One-way air flow design allows air to escape without allowing moisture in. Made of lightweight and durable plastic.

Venting

Part Number	Description
DS-683	"Weather-Tight" s/a vent - black
DS-683W	"Weather-Tight" s/a vent - white
DS-683SP W	4" X 5" solar powered s/a vent white
DS-STEALTH	Self-piercing louvered vent
DS-062A	Round airlette self-adhesive vent
DS-683WP	4" X 5" wind powered s/a vent