

Grade L Windlass Chain - G30



Grade L is a low carbon steel chain specifically manufactured to Australian Standard AS2321-2006. Used for anchoring and mooring applications, Grade L calibrated short-link design ensures proper fit for most Australian windlasses. Hot dip galvanized for the best protection against corrosion and abrasion. Check manufacturer's specification prior to purchase.

Finish: Hot Dip Galvanized

Packaging: Full & Half Drums, and Pails

Exceeds NACM, RR-C-271D specifications

Trade Size mm	Wire Diameter		Inside Dimensions				Working Load Limit	
	mm	in.	Length		Width		kg-force	pound-force
			mm	in.	mm	in.		
6	6	.24	18	.71	7.5	.3	454	1000
8	8	.31	24	.94	10	.39	816	1800
10	10	.39	30	1.2	12.5	.49	1270	2800
13	13	.51	39	1.5	16.3	.64	2041	4500

Trade size mm	Plastic Pail					Half Drum					Full Drum				
	Weight		Length		Part ID	Weight		Length		Part ID	Weight		Length		Part ID
	Kg	Lbs	m	ft.		Kg	Lbs	m	ft.		Kg	Lbs	m	ft.	
6	48	106	60	196.9	10315930	126	276	157	515	10315928	252	554	315	1033.5	10315929
8	48	106	34	111.6	10315766	125	275	88	288.7	10315932	249	547	175	574.1	10315931
10	50	110	22	72.2	10315756	125	276	55	180.4	10315925	251	552	110	361	10315924
13	50	110	13	42.7	10315759	124	272	32	105	10315926	247	543	64	210	10315927

Please see page 3 for packaging details.

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications