

SELF-RIGHTING ANCHOR SWIVELS

NEW!



- Flip swivel – rotates anchor into the correct orientation if it retrieves over the bow upside-down
- Covers the size ranges from Rocna®/Vulcan® Anchors 6Kg through 55Kg
- Highest work load of any self-righting swivel on the market
- Will fit imperial and metric chain
- Unique in the market, meets the same load specs even in side load
- Stainless Steel Grade: 17-4PH which is stronger than 316 while still offering excellent corrosion resistance
- Polished mirror finish
- Hardware included: loctite hexagon socket set screws, allen key, installation instructions

The following chain sizes are recommended based on the anchor specifications:

PID/ DESCRIPTION	LENGTH in	ANCHOR/CHAIN SLOT WIDTH in	ANCHOR SIZE kg	RECOMMENDED G40 CHAIN	WORKING LOAD LIMIT lb
TS31SU01 Type 1	4.2	0.56/ 0.39	Vulcan® & Rocna® 6-15 kg	1/4", 5/16", 7-8 mm	3900
TS31SU03 Type 3	4.36	0.74 / 0.516	Vulcan® & Rocna® 15-33 kg	5/16", 3/8", 9-11 mm	5400
TS31SU05 Type 5	5.02	0.844 / 0.516	Vulcan® & Rocna® 25-55 kg	5/16"-7/16", 10-11 mm *	7200

* Minimum size 5/16" is not recommended, as it is too small a chain for that size of anchor, yet it will fit chains down to 5/16".

Please check manufacturer's specification prior to use. Design subject to change.

CMP

CMP Group Ltd.

sales@cmpgroup.net | cmpgroup.net